

Trockner	Einlass		Entspanne	Spannung	Eingangs- Ausgangsanschluss	Betriebsleistung	Abmessungen						Ca. Gewicht	
	Durchfluss													
	Modell	SCFM	NM³/H	PSI			kW	H		W		D		
					IN		IN	MM	IN	MM	IN	MM	LB	KG
FLX 1.1	7,5	127	2,9	115/1/60	NPT 1"	0.54	30	751	14	363	24	603	120	54.5
FLX 1.2	10,0	170	3,0	115/1/60	NPT 1"	0.62	28	711	14	363	31	781	147	66.5
FLX 15.1	150	255	36	115/1/60	NPT 2"	10,4	30	761	17	443	36	901	189	85.5
FLX 2.1-4	200	340	2,2	460/3/60	NPT 2"	126	30	761	18	443	38	961	217	98.5
FLX 3.1	300	509	36	460/3/60	NPT 2"	1.99	36	911	19	493	44	1111	324	147
FLX 4.5	450	765	3,0	460/3/60	NPT 2"	3,23	36	911	19	493	44	1111	335	152
FLX 5.5	550	935	3,0	460/3/60	NPT 2"	34.2	41	1032	20	494	49	1253	396	180
FLX 8.1	800	1300	3,7	460/3/60	FLG 3"	4.3								
FLX 10.1	1000	1700	5,0	460/3/60	FLG 3"	5.84								
FLX 12.5	1250	2150	46	460/3/60	FLG 4"	7.6								
FLX 15.1	1500	2,550	3,9	460/3/60	FLG 4"	900								
FLX 20.1	2000	3400	31	460/3/60	FLG 4"	1000								

Die Leistungsdaten wurden gemäß ISO 7183 (Option A2) angegeben: 100°F Eintrittstemperatur, 100°F Umgebungstemperatur und 100 psig Bedingungen.