

Modelle RDH115 - RDH5400G

MODELL	EINLAUF DURCHFLUSS	FLOW OUTLET		Betriebsdruck	Max. IN / OUT VERBINDUNGEN	ABMESSUNGEN (ZOLL)				Gewicht
		@ -40°F P.D.P	@ -100°F P.D.P.							
		SCFM ¹	SCFM ¹			H	W	D	LBS	
RDH115	115	98	97	150	1" NPT	90	40	34	650	
RDH165	165	14,1	140	150	1 1/2" NPT	90	40	34	825	
RDH260	260	223	220	150	2" NPT	90	42	47	1350	
RDH370	370	317	312	150	2" NPT	90	42	60	1650	
RDH450	450	385	380	150	2" NPT	92	42	60	1800	
RDH590	590	505	498	150	2" NPT	95	50	70	2860	
RDH750	750	642	634	150	2 1/2" NPT	97	58	72	3450	
RDH930	930	796	786	150	2 1/2" NPT	105	58	72	3800	
RDH930G	930	796	786	150	2 1/2" NPT	80	76	73	3500	
RDH1130	1130	967	955	150	3" NPT	105	58	72	4300	
RDH1350	1.35	1156	1141	150	3" NPT	109	58	72	4700	
rdh1550	1550	1327	1309	150	3" Chef	100	78	96	5000	
rdh1550G	1550	1327	1309	250	3" Chef	79	78	83	5500	
RDH2100	2100	1797	1774	150	3" Chef	106	80	73	6900	
RDH2100G	2100	1797	1774	150	3" Chef					
RDH3000	3000	2567	2534	150	3" Chef					
RDH3000G	3000	2567	2534	150	2" x 3" Chef					
RDH4100	4100	3465	3445	150	6" FLG					
RDH5400	5400	4620	4561	150	6" FLG					
RDH5400G	5400	4620	4561	150	4" x 3" Chef					

Der angegebene Durchfluss basiert auf Eingangsdruckluft bei 100 psig und 100°F

Modelle RDHHP495 - RDHHP5200G - Hochdruck bei 350 PSIG

MODELL	EINLAUF DURCHFLUSS	FLOW OUTLET		Betriebsdruck	Max. IN / OUT VERBINDUNGEN
		@ -40°F P.D.P	@ -100°F P.D.P.		
		SCFM ¹	SCFM ¹		
RDHHP495	900	828	818	365	3" NPT
RDHHP715	1300	1196	1186	365	3" NPT
RDHHP1550G	2800	2576	2,550	365	3" Chef
RDHHP5200G	9300	8530	8400	365	4" x 3" Chef